

Key Features

65" screen size with 4K (3840 x 2160) resolution
| Increased accuracy and a sleek touchscreen experience with InGlass™ Technology | 20-point touch | Pre-installed vBoard annotation, ViewBoard® Cast content sharing, and Zoom conference software | FIPS201 certified high security fingerprint reader



Product Description

The ViewBoard® IFP6560 is a 65" 4K (3840 x 2160) interactive flat panel display with an open platform design and diverse collaborative capabilities. ViewBoard® IFP6560 is fit for integration into Google-based & Chrome environments, offers seamless Windows accessories & office365 compatibility, and comes equipped with Mac multi-touch gesture mirroring (driver needed). InGlass™ technology delivers a more accurate and sleek touchscreen experience with lag-free writing and drawing in two colors with different thicknesses. Pairing ViewBoard® IFP6560's 20-point touch display with pre-installed tools, such as vBoard for annotation, ViewBoard® Cast for content sharing, and Zoom conference software, allows multiple users to remotely write, share, and interact simultaneously. Connecting to more powerful computing platforms is possible via the board's dual PC slots for the optional Intel United® certified OPS* (Open Pluggable Specification) which allows users to switch their system to Windows OS. Connecting to the board is made easy through SmartPort™ shared front USB ports for internal and external PCs. Finger print recognition bolsters security and enables easy login to Windows or myViewBoard™ for your digital whiteboard in the cloud. Versatile connectivity to a multitude of devices combined with VESA-compatibility and a trolley design allows for flexible installation anywhere, no matter the occasion. *ViewSonic OPS VPC12-WPO

Visit Us - www.viewsonic.com

LCD PANEL

Panel Size:	65"
Type/ Tech:	TFT LCD Module with DLED Backlight
Display Area (mm):	1428.48(H) x 803.52(V) mm (64.5" diagonal)
Aspect Ratio:	16:09
Resolution:	3840 x 2160
Colors:	1.07B (8Bit+FRC)
Brightness:	350 nits (typ.)
Contrast Ratio:	4000:1 (typ.)
Response Time:	8 ms
Viewing Angles:	H = 178, V = 178 (typ.)
Backlight:	DLED
Backlight Life:	30,000 Hours Min.
Hardness:	7H

TOUCH

Type/ Tech:	Flatfrog InGlass IR
Touch Resolution:	22855 x 12856
Touch Point:	20 points touch, 10 points writing
Response Time:	6.7ms
System:	Win 7pro/Ultimate/8/8.1/10, Chrome OS Linux kernel 3.15 or later, Android 4.4 with linux kernel 3.15 or later, Linux OS kernel 3.15 or later, Mac OS 10.10 or later

INPUT

HDMI:	1 x HDMI 1.4a, 4K@30Hz, support CEC on/off, HDCP 1.4 2 x HDMI 2.0, 4K@60Hz, support CEC on/off, HDCP 2.2
RGB / VGA:	x 1
DisplayPort:	x 1 (4K@30Hz)
Audio:	x 1 PC audio (3.5mm)
CVBS (AV):	x 1
RS232:	x 1
PC Slot:	x 1 (Intel OPS)

OUTPUT

HDMI:	x 1 HDMI 2.0, 4K@60Hz, no CEC support
Audio (Earphone out):	x 1
SPIDF:	x 1
RS232:	x 1

LAN

RJ45:	x 1
-------	-----

USB

2.0 Type A:	x 3 (front x 2, for both embedded player and slot-in PC)
3.0 Type A:	x 2
2.0 Type B (For touch):	x 2 (front x 1 for HDMI 1.4; back side x 1 for HDMI2.0, DP, VGA)

SPEAKERS

10W x 2

BUILT-IN PC

Processor:	ARM Cortex A53 Quad Core 1.4G Hz CPU
Graphic:	ARM Mali-450 MP4 Quad Core
Memory:	2GB DDR3
Storage:	16GB eMMC
Networking:	10/100M auto-identification and DHCP

COMPATIBILITY

VGA:	Refer to timing table
HDMI:	3840x2160
DP:	3840x2160

POWER

Voltage:	100V-240V,50/60Hz (AC)
Consumption:	210 W (without OPS) 270 W (With OPS)

ERGONOMICS

Wall Mount (VESA®):	600 x 400mm; Screw: M8 x 25mm
---------------------	-------------------------------

OPERATING CONDITIONS

Temperature (° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% ~ 80% non-condensing

DIMENSIONS

Physical w/o Stand (mm / inch):	1565.5 x 967.1 x 94.5 mm / 61.63 x 38.07 x 3.72 inch
Packaging (mm / inch):	1715 x 1100 x 280 mm / 67.52 x 40.31 x 11.02 inch

WEIGHT

Net w/o Stand (kg / lb):	48.5kg/106.9lb
Gross (kg / lb):	61kg/134.5lb

REGULATIONS

Standard:	FCC, CE, cTUVus,CB, RoHS, WEEE
-----------	--------------------------------

WHAT'S IN THE BOX?

1. HDMI cable(1.5 meters)
2. Power cable(3 meters) x 4 (A+E+M+U)
3. Remote control with AA battery
4. USB cable(1.8 meters)
5. Touch pen x 2
6. Quick Start Guide & Compliance statement
7. Webcam Plate
8. Wall mount Screw x 4