

Sir Safety System S.p.A. Single-member company
Wholly-owned subsidiary of Sir Holding Srl
Via dei Fornaciai, 9 - Santa Maria degli Angeli
06081 Assisi - Perugia - Italy
Tel.+39 075.8043737 (R.A.) - Fax +39 075.8048686

VAT Nr. IT 03359340548
Viale Europa 74
20090 Cusago Milano
Tel. +39 02.90394575 (R.A.)
Fax +39 02.90394441

export@sirsafety.com
www.sirsafety.com

COMPANY WITH
QUALITY SYSTEM
CERTIFIED
= ISO 9001 =

Name: FA1321 Premium Respirator FFP2 NR D With Exhalation Valve	Code: 45191	FA13 RESPIRATORY PROTECTION DISPOSABLE MASKS FFP2
--	--------------------	--

Description

Disposable Premium respirator with exhalation valve. Suitable for medium toxicity environments up to 12 times the TLV.
Pack of 10 pieces.

- Latex-free elastic straps, do not cause skin allergies.
- While not in use, thanks to its shape, the respirator remains in upright position, avoiding the accumulations of polluting agents in the inner part in contact with the face.
- Better face adaptability, due to its concave shape.
- Completely metal-free to prevent rusting.
- Greater protection from fine and toxic dusts, due to its new filter surface which passed the D test. This test is performed with Dolomite dusts and certifies a higher level of protection with added anti-clogging properties.

The product has been designed and manufactured to comply with Regulation (EU) 2016/425 and subsequent amendments, and to conform to the requirements of EN 149.
It is classified as PPE Cat. III.

FFP2 NR D

FFP2: Nominal Protection Factor: 12

Operational Protection Factor: 10

NR: disposable

D: The respirator has passed the dolomite clogging test.



Category III	Colours White	Available Sizes unica
Quantity/Carton 120	Important Information Make sure the product is in good condition and undamaged before use. Once you become aware of a damage, you should immediately replace it.	Recommended for Protects against solid and liquid aerosols in concentrations up to 12 times the TLV. Suitable for demolition and cutting of plaster, bricks and tiles, metal burring.
Dexterity	EC Standards EN 149 CE Class:FFP2 NR D	Storage and cleaning Keep in a cool dry place, far from heat sources.